

Canftech® TY-MB-2

TY MB-2 Electronic Grade Mixed Bed Resin



IEX Resin
Mixed bed Exchange Resin

Basic Features

Principal Applications	Electronic industry, dental instrument, laboratory
Polymer matrix structure:	Gel polystyrene crosslinked with divinylbenzene
Appearance:	Amber color spherical beads
Functional Group:	Sulfonic Acid / Type I Quaternary Ammonium
Ionic form as shipped:	H ⁺ / OH ⁻

Description:

Canftech® TY MB-2 is a high quality ionically equilibrated mixed bed resin composed of strong acid cation resin in H⁺ form and strong base type 1 anion resin in OH⁻ form. Ready to use as supplied. It is designed for production of high purity water and other applications requiring DI water, such as semiconductor and micro electronic industry, DI water for laboratory, refining after RO system, etc. It can achieve almost complete reduction of TDS and resistivity >15 mega Ohm. Carbon dioxide could carbonate the hydroxide sites of anion component, so it is important to avoid exposure to atmosphere for long period.

Physical and Chemical Properties:

NO.	ITEM	SPEC
1	Cation / Anion volumetric ratio	1/1.5
2	Moisture content (%)	52-57
3	Total exchange capacity (eq/L)	0.6
4	Particle size range (%)	0.315-1.25mm>95
5	Specific density (g/ml)	1.06-1.22
6	Uniformity Coefficient	<1.7
7	Shipping Weight (g/ml)	0.69-0.75
8	Whole beads after attrition (%)	>95
9	Storage temperature (°C)	0-40

Suggested Operating Conditions:

NO.	ITEM	SPEC
1	Max operating temp	60°C / 140°F
2	Minimum bed depth	600mm
3	Service flow rate	20- 40 BV/h
4	Applicable PH	1-14

Packaging:

- 25liter PE bags; 48bags/Pallet
- 5Liter Aluminum foil vacuum bag, 5bags/carton

Regulatory Approvals:

